


Glasdon TOPSY ROYALE

With Keyed Lock System

Operating Instructions



Insert the key all the way into the lock. (Do not turn the key.) This will automatically release the locking mechanism.






With the key still in position, turn body counter-clockwise, and lift body over liner. (See note A)



Remove the key at this stage.



5 Lift liner out of plinth, empty and place back into plinth. Ensure handles drop outside the liner.



Lift body over liner and lower to rest on plinth, turn body clockwise to lock.

- A planned maintenance schedule of regular inspection is recommended, replacing components as necessary.
- Replacement components are available direct from GLASDON, Inc.
- GLASDON, Inc. cannot be held responsible for claims arising from incorrect installation, unauthorized modifications or misuse of the product.

Glasdon and topsy royale are trademarks of Glasdon Group or its SUBSIDIARIES IN THE U.K. AND OTHER COUNTRIES

Tssue 1 August 2012

©Copyright 2013

C000/0424

Glasdon reserve the right to alter specifications without prior notice.

PLEASE NOTE

Prior to installation and removal of the body it may be necessary for an assistant to firmly hold plinth while the operator maneuvers the body in accordance with the attached operating instructions.

The Topsy Royale must be ground fixed or ballasted to maximize the performance of Glasdon's unique Locking System.

Regular cleaning is essential to maintain the pristine appearance of this quality product. All surfaces of the unit should be regularly cleaned with warm, soapy water and thoroughly rinsed. This is important in maintaining both the outward appearance of the product and ensuring ease of operation.

Any damaged components should be replaced. Spares are available direct from Glasdon Inc.

Glasdon Inc. cannot be held responsible for claims arising from incorrect installation, unauthorized modification or misuse of the product.



5200D Anthony Road Sandston VA 23150

Sales Inquiries: 1-855-USGLASDON General Inquiries: 804-726-3777

Fax: 804-726-3778 E-mail: info@glasdon.com Web: www.glasdon.com